Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-186-6727

Section Quantity: 2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 1.094 inches Shaft Diameter: Between 0.248 inches and 0.251 inches Shaft Length: 0.875 inches **Mounting Bushing Length:** 0.500 inches **Body Length:** 1.266 inches Shaft Style: Round, slotted Actuator Type: Single shaft **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Locking bushing

Electrical Resistance Per Section:

500.000 kilohms all sections

Rotary Actuator Travel In Angular Deg:

Between 309.0 and 320.0

Resistance Tempurature Characteristic Range Per Section In Percent:

-3.0/+0.0 -55 degrees celsius all sections and -5.0/+10.0 -25 degrees celsius all sections and -5.0/+10.0 25 degrees celsius all sections and

+0.0/+3.0 120 degrees celsius all sections

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 all sections

NSN 5905-01-186-6727 Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:

2.0 free air all sections

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 all sections

Actuator Travel Control Feature:

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

Standard Taper Curve Per Section:

A all sections

Test Data Document:

81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

6 tab, solder lug

Specification Data:

81349-mil-r-94/6 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0