Nonprecision Wire Wound Variable Resistor - Page 1 of 2



## View Online at https://aerobasegroup.com/nsn/5905-01-187-6042 Section Quantity: 1 **Body Style:** Cylindrical **Reliability Indicator:** Not established **Body Diameter:** 0.781 inches **Body Length:** 0.391 inches Actuator Type: Flush drive with slot-hole Effective Electrical Rotation In Deg Angular Rotation: 270.0 Maximum Starting Torque: 10.00 inch-ounces Maximum Running Torque: 10.00 inch-ounces Maximum Stop Torque: 64.00 inch-ounces **Terminal Location:** Rear end **Mounting Method:** Tab **Features Provided:** Grounded contact arm **Electrical Resistance Per Section:** 2.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 270.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 single section **Power Dissipation Rating Per Section In Watts:** 2.0 free air single section **Resistance Tolerance Per Section In Percent:** -20.0/+20.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 55.0 single section **Standard Taper Curve Per Section:** A single section



## Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0