

View Online at <https://aerobasegroup.com/nsn/5905-01-187-8809>

**Reliability Indicator:**

Not established

**Terminal Length:**

1.500 inches

**Body Length:**

0.150 inches

**Body Outside Diameter:**

0.125 inches

**Terminal Diameter:**

0.013 inches

**Maximum Power Dissipation Rating:**

350.00 milliwatts

**Ambient Temperature At Full Rated Power:**

25.0 degrees celsius

**Maximum Operating Temp:**

125.0 degrees celsius

**Thermal Time Constant In Seconds:**

14.0

**Power Dissipation Constant In Milliwatts Per Deg Celsius:**

2.0

**Zero Power Temperature Coefficient Of Resistance In Percent Per Deg Celsius:**

29.58

**Temperature Points For Resistance Readings At Zero Power:**

75.0 degrees celsius 6th resistance-temperature point

**Zero Power Resistance At Specificationified Temp:**

147.7 ohms 6th resistance-temperature point

**Resistance Tolerance At A Specificationified Temperature In Percent:**

-10.0/+10.0 all resistance-temperature points

**Inclosure Type:**

Encapsulated

**Cubic Measure:**

0.002 cubic inches

**Zero Power Resistance:**

1.000 kilohms

**Zero Power Resistance Tolerance In Percent At Reference Temp:**

-10.0/+10.0

**Reference Temperature In Deg Celsius:**

25.0

**Style Designator:**

Sealed or coated bead

**Test Data Document:**

37695-238283 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

2 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A086a0