

View Online at <https://aerobasegroup.com/nsn/5905-01-188-2299>

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

First Flat Length:

0.600 inches

Flat Height:

Between 0.211 inches and 0.221 inches

Body Diameter:

1.030 inches

Shaft Diameter:

Between 0.248 inches and 0.251 inches

Shaft Length:

0.630 inches

Mounting Bushing Length:

0.380 inches

Body Length:

2.000 inches

Shaft Style:

Round, flatted

Shaft Bearing Type:

Sleeve

Switch Type:

Rotary

Actuator Type:

Single shaft

Nonturn Device Location:

At 6 oclock

Nonturn Device Radius:

Between 0.410 inches and 0.450 inches

Switch Contact Arrangement:

Double pole, double throw

Fragility Factor:

Moderately rugged

End Application:

B-1b aircraft

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Rear end

Mounting Method:

Standard bushing

Features Provided:

Switch

Actuator Travel Control Feature:

Stops

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

10 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0