

View Online at <https://aerobasegroup.com/nsn/5905-01-188-6823>

**Section Quantity:**

1

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

0.3750 inches

**Pilot Length:**

0.0620 inches

**Overall Length:**

2.056 inches

**Undercut Diameter:**

0.400 inches

**Undercut Width:**

0.0620 inches

**Body Diameter:**

0.500 inches

**Shaft Diameter:**

0.0935 inches

**Shaft Length:**

0.625 inches

**Body Length:**

1.431 inches

**Overall Diameter:**

0.672 inches

**Mounting Lip Diameter:**

0.5000 inches

**Mounting Lip Depth:**

0.0620 inches

**Shaft Style:**

Round, slotted

**Shaft Bearing Type:**

Ball

**Actuator Type:**

Single shaft

**Maximum Starting Torque:**

0.50 inch-ounces

**Maximum Running Torque:**

0.30 inch-ounces

**Shaft End Play:**

0.005 inches

**Shaft Runout:**

0.003 inches

**Lateral Runout:**

0.003 inches

**Pilot Diameter Runout:**

0.002 inches

**Shaft Radial Play:**

0.002 inches

**Fragility Factor:**

Moderately rugged

**Terminal Location:**

Longitudinally positioned on the circumference

**Mounting Method:**

Clamp ring

**Electrical Resistance Per Section:**

10.0 percent, rated amperes c and better flooring

**Rotary Actuator Travel In Angular Deg:**

5400.0

**Function Conformity Tolerance Per Section:**

-0.50/+0.50 single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

125.0 single section

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-50.0/+50.0 single section

**Power Dissipation Rating Per Section In Watts:**

1.0 7th secondary quality

**Function Conformity Per Section:**

Single section independent linearity

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

**Actuator Travel Control Feature:**

Clutch

**Function Characteristic Per Section:**

7 oclock all primaries

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 single section

**Precious Material And Location:**

Terminal surfaces gold

**Precious Material:**

Gold

**Test Data Document:**

96214-805179 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

1 tab, solder lug and 2 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0