

View Online at <https://aerobasegroup.com/nsn/5905-01-189-1208>

**Section Quantity:**

1

**Body Style:**

Rectangular w/mounting holes/slots

**Reliability Indicator:**

Established

**Reliability Failure Rate Level In Percent:**

1.000

**Mounting Hole Diameter:**

0.093 inches

**Body Length:**

Between 1.240 inches and 1.260 inches

**Body Width:**

Between 0.180 inches and 0.200 inches

**Body Height:**

Between 0.300 inches and 0.330 inches

**Contact Arm Electrical Off Position:**

Fully ccw

**Actuator Type:**

Flush drive with slot-hole

**Effective Electrical Rotation In Deg Angular Rotation:**

Between 6120.0 and 9720.0

**Lateral Distance Between Mounting Hole Centers:**

1.000 inches

**Mounting Facility Quantity:**

2

**Terminal Location:**

Rear end

**Mounting Method:**

Unthreaded hole

**Electrical Resistance Per Section:**

200.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

9720.0

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

150.0 single section

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-100.0/+100.0 single section

**Power Dissipation Rating Per Section In Watts:**

0.75 free air single section

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

**Actuator Travel Control Feature:**

Clutch

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

85.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

3 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0