## NSN 5905-01-189-9212

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-189-9212 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.896 inches **Body Diameter:** 0.750 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.812 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 1.084 inches **Overall Diameter:** 0.890 inches **Undercut Diameter:** 0.125 inches **Shaft Style:** Round, stepped **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 275.0 and 285.0 **Maximum Starting Torque:** 6.00 inch-ounces **Maximum Running Torque:** 6.00 inch-ounces **Maximum Stop Torque:** 80.00 inch-ounces **Fragility Factor:** Moderately rugged **Undercut Length:** 0.437 inches **Screw Thread Diameter:** 0.375 inches

Screw Thread Series Designator:

Unef

## NSN 5905-01-189-9212

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Features Provided:
Panel seal
Electrical Resistance Per Section:
10.000 percent, rated amperes c and better
Rotary Actuator Travel In Angular Deg:
Between 275.0 and 285.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 all sections
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-250.0/+250.0 all sections
Power Dissipation Rating Per Section In Watts:
1.3 7th secondary at 10'30 oclock
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 all sections
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 all sections
Standard Taper Curve Per Section:
A all sections
Special Features:
White stop plates celenex 3310
Test Data Document:
10138-15773 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A002a0