## NSN 5905-01-190-1275

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-190-1275 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.482 inches First Flat Length: 0.250 inches Flat Height: 0.218 inches **Body Diameter:** 3.000 inches **Shaft Diameter:** Between 0.2494 inches and 0.2497 inches **Shaft Length:** 1.500 inches **Mounting Bushing Length:** 0.500 inches **Body Length:** 0.982 inches **Overall Diameter:** 3.500 inches **Shaft Style:** Round, flatted **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation: Maximum Starting Torque:** 1.50 inch-ounces **Maximum Running Torque:** 1.20 inch-ounces **Shaft End Play:** 0.005 inches **Shaft Runout:** 

0.0005 inches **Lateral Runout:**0.004 inches

## NSN 5905-01-190-1275

Precision Wire Wound Variable Resistor - Page 2 of 3



Pilot Diameter Runout:		
0.002 inches		
Shaft Radial Play:		
0.004 inches		
Fragility Factor:		
Moderately rugged		
Screw Thread Diameter:		
0.500 inches		
Screw Thread Series Designator:		
Unef		
Screw Thready Qty Per Inch (tpi):		
32.0		
Terminal Location:		
Radially positioned over less than half the circumference		
Mounting Method:		
Standard bushing		
Features Provided:		
Humidity proof		
Cubic Measure:		
7.089 cubic inches		
Electrical Resistance Per Section:		
1.0 percent, rated amperes c and better flooring		
Rotary Actuator Travel In Angular Deg:		
360.0		
Function Conformity Tolerance Per Section:		
-0.50/+0.50 single section		
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:		
85.0 single section		
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:		
-130.0/+130.0 single section		
Power Dissipation Rating Per Section In Watts:		
5.0 7th secondary quality		
Function Conformity Per Section:		
Single section independent linearity		
Resistance Tolerance Per Section In Percent:		
-5.0/+5.0 single section		
Actuator Travel Control Feature:		
Continuous motion		
Function Characteristic Per Section:		
7 oclock all primaries		
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:		
40.0 single section		
Terminal Type And Quantity:		

3 turret

## NSN 5905-01-190-1275

Precision Wire Wound Variable Resistor - Page 3 of 3



Shelf	Life:
N/a	

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0