## NSN 5905-01-190-6298

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-190-6298

### Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-100.0 to 100.0

**Electrical Resistance:** 

1.470 kilohms

**Resistance Tolerance In Percent:** 

-1.000 to 1.000

Ambient Tempurature In Deg Celsius At Full Rated Power:

### 70.0

Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

150.0

Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0 to 150.0

**Inclosure Method:** 

Encapsulated

**Terminal Type:** 

Wire lead

Mil-std-1276 Wire Lead Type Designator:

```
С
```

**Reliability Indicator:** 

Established

**Reliability Failure Rate Level In Percent:** 

0.001

**Terminal Length:** 

1.500 inches

#### **Body Diameter:**

0.138 inches

**Body Length:** 

0.375 inches

**Power Dissipation Rating In Watts:** 

0.500 free air

Unpackaged Unit Weight:

0.750 grams

#### Style Designator:

Axial terminal each end

### Test Data Document:

81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Specification Data:**

81349-mil-r-39017/2 government specification

Shelf Life:

N/a

# NSN 5905-01-190-6298

Film Fixed Resistor - Page 2 of 2

Demilitarization:

No

Fiig:

A001a0

