NSN 5905-01-191-3583

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-191-3583		
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:		
-5.0/+5.0 first temp coefficient		
Electrical Resistance:		
1.000 kilohms		
Resistance Tolerance In Percent:		
-0.050/+0.050		
Ambient Tempurature In Deg Celsius At Full Rated Power:		
125.0		
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:		
175.0		
Tempurature Range Of Tempurature Coefficient In Deg Celsius:		
-55.0/+125.0 temp range of first temp coefficient		
Inclosure Method:		
Encapsulated		
Terminal Type:		
Wire lead		

Mil-std-1276 Wire Lead Type Designator:

С

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

0.010

Terminal Length:

1.905 inches

Body Length:

0.336 inches

Body Width:

Between 0.290 inches and 0.320 inches

Body Height:

Between 0.095 inches and 0.120 inches

Power Dissipation Rating In Watts:

0.300 free air

Cubic Measure (non-core):

0.013 cubic inches

Unpackaged Unit Weight:

1.000 grams

Style Designator:

Terminals one edge

Test Data Document:

81349-mil-prf-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-prf-55182/9 government specification

NSN 5905-01-191-3583

Film Fixed Resistor - Page 2 of 2



Shelf	Life:
N/a	
11::4 6	S

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A001a0

Mil-std (military Standard):

Mil-prf-55182 spec.