# NSN 5905-01-191-9611

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-191-9611

## Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-100.0/+100.0 first temp coefficient

## **Electrical Resistance:**

22.000 kilohms

## **Resistance Tolerance In Percent:**

-2.000/+2.000

## Ambient Tempurature In Deg Celsius At Full Rated Power:

### 70.0

## Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

150.0

#### Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+150.0 temp range of first temp coefficient

#### **Inclosure Method:**

Encapsulated

#### **Terminal Type:**

## Wire lead

**Reliability Indicator:** 

#### Established

**Reliability Failure Rate Level In Percent:** 

0.001

#### **Terminal Length:**

1.250 inches

#### **Body Diameter:**

0.066 inches

#### **Body Length:**

0.150 inches

#### **Power Dissipation Rating In Watts:**

0.125 free air

#### Cubic Measure (non-core):

0.002 cubic inches

#### **Nuclear Hardness Critical Feature:**

Hardened

#### **Unpackaged Unit Weight:**

0.300 grams

#### Style Designator:

Axial terminal each end

#### **Test Data Document:**

81349-mil-prf-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

81349-mil-prf-39017/5 government specification

### Shelf Life:

N/a

# NSN 5905-01-191-9611

Film Fixed Resistor - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A001a0

Mil-std (military Standard):

Mil-prf-39017 spec.

