NSN 5905-01-192-2206

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-192-2206 **Section Quantity:** 2 **Body Style:** Rectangular bushing mounted **Reliability Indicator:** Not established **Shaft Diameter:** 0.250 millimeters **Shaft Length:** 1.580 millimeters **Mounting Stud Length:** 0.500 millimeters **Mounting Bushing Length:** 0.375 inches

Body Length:

1.047 millimeters

Body Width:

1.047 inches

Body Height:

0.625 inches

Undercut Diameter:

0.125 millimeters

Shaft Style:

Round, stepped

Actuator Type:

Dual concentric

Undercut Length:

1.125 millimeters

Screw Thread Diameter:

0.375 millimeters

Screw Thread Series Designator:

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Longitudinally positioned on the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

2000.000 ohms c and better finish

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 all sections

NSN 5905-01-192-2206

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissipation	Rating Per	Section	In Watts:
-------------------	------------	---------	-----------

1.0 free air all sections

Resistance Tolerance Per Section In Percent:

-0.10/+0.10 all sections

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A002a0