NSN 5905-01-192-4307

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-192-4307

Section Quantity:
1
Body Style:
Rectangular w/bushing
Reliability Indicator:
Not established
Overall Length:
1.453 inches
Overall Height:
0.938 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.750 inches
Mounting Bushing Length:
0.250 inches
Body Length:
0.469 inches
Body Width:
0.500 inches
Body Height:
0.735 inches
Shaft Style:
Round, slotted
Switch Type:
Rotary
Switch Voltage Rating In Volts:
125.0 and 28.0
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
248.0
Maximum Starting Torque:
8.00 inch-ounces
Maximum Running Torque:
3.00 inch-ounces
Maximum Stop Torque:
64.00 inch-ounces
Mechanical Backlash In Deg Angular Rotation:
3.0
Switch Operating Position:

Start of rotation

NSN 5905-01-192-4307

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Switch Contact Arrangement:
Single pole, single throw, normally closed
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear-bottom
Mounting Method:
Standard bushing
Features Provided:
Switch
Electrical Resistance Per Section:
1.000 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:
295.0
Resistance Tempurature Characteristic Range Per Section In Percent:
+0.0/+6.9 -55 degrees celsius single section and +0.0/+3.8 -25 degrees celsius single section and +0.0/+1.9 0 degrees celsius single section
and -2.5/+2.5 85 degrees celsius single section and +0.0/+5.6 120 degrees celsius single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
170.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 7th secondary quality
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Switch Current Type And Rating In Amps:
0.500 ac and 1.500 dc
Standard Taper Curve Per Section:
C single section
Terminal Type And Quantity:
5 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No