NSN 5905-01-192-7086

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-192-7086

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-50.0 to 50.0

Electrical Resistance:

45.900 kilohms

Resistance Tolerance In Percent:

-0.100 to 0.100

Ambient Tempurature In Deg Celsius At Full Rated Power:

125.0

Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

175.0

Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0 to 175.0

Inclosure Method:

Encapsulated

Terminal Type:

Wire lead

Mil-std-1276 Wire Lead Type Designator:

```
С
```

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

0.001

Terminal Length:

Between 1.375 inches and 1.625 inches

Body Diameter:

Between 0.078 inches and 0.140 inches

Body Length:

Between 0.204 inches and 0.281 inches

Power Dissipation Rating In Watts:

0.100 free air

Style Designator:

Axial terminal each end

Test Data Document:

81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-r-55182/1 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5905-01-192-7086

Film Fixed Resistor - Page 2 of 2

Fiig: A001a0

