# NSN 5905-01-192-7087

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-192-7087

# Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-50.0 to 50.0

**Electrical Resistance:** 

47.000 kilohms

**Resistance Tolerance In Percent:** 

-0.100 to 0.100

Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 125.0

Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

175.0

Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0 to 275.0

**Inclosure Method:** 

Encapsulated

**Terminal Type:** 

Wire lead

Mil-std-1276 Wire Lead Type Designator:

С

Reliability Indicator:

Established

**Reliability Failure Rate Level In Percent:** 

0.001

Terminal Length:

Between 1.375 inches and 1.625 inches

### **Body Diameter:**

Between 0.078 inches and 0.140 inches

### Body Length:

Between 0.204 inches and 0.281 inches

# **Power Dissipation Rating In Watts:**

0.100 free air

### Style Designator:

Axial terminal each end

### Test Data Document:

81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Specification Data:**

81349-mil-r-55182/1 government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

# NSN 5905-01-192-7087

Film Fixed Resistor - Page 2 of 2

**Fiig:** A001a0

