Nonprecision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-192-8618

Section Quantity:

1

Body Style:

Rectangular bushing mounted

Reliability Indicator:

Not established

Overall Length:

1.141 inches

Terminal Length:

0.500 inches

Overall Height:

1.125 inches

Overall Width:

0.625 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.547 inches

Mounting Bushing Length:

0.250 inches

Body Length:

0.594 inches

Body Width:

0.625 inches

Body Height:

0.625 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

260.0

Maximum Starting Torque:

2.50 inch-ounces

Maximum Running Torque:

2.50 inch-ounces

Maximum Stop Torque:

64.00 inch-ounces

Center To Center Distance Between Terminals:

0.200 inches



Fragility Factor:

Moderately rugged

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Lower adjacent side two rows

Mounting Method:

Standard bushing

Center To Center Distance Between Terminal Rows:

0.100 inches

Cubic Measure:

0.232 cubic inches

Electrical Resistance Per Section:

2.5 gallons per minute c and better flooring

Rotary Actuator Travel In Angular Deg:

300.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

Resistance Tempurature Characteristic Range Per Section In Percent:

+0.0/+10.0 -55 degrees celsius single section and +0.0/+5.0 -25 degrees celsius single section and +0.0/+2.5 0 degrees celsius single

section and -3.5/+3.5 85 degrees celsius single section and +0.0/+7.5 120 degrees celsius single section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 7th secondary quality

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5905-01-192-8618 Nonprecision Nonwire Wound Variable Resistor - Page 3 of 3

d Variable

Fiig: A002a0

