

View Online at <https://aerobasegroup.com/nsn/5905-01-193-4914>

**Section Quantity:**

2

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**First Flat Length:**

0.375 inches

**Flat Height:**

0.216 inches

**Body Diameter:**

0.750 inches

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

0.750 inches

**Mounting Bushing Length:**

0.250 inches

**Body Length:**

2.000 inches

**Shaft Style:**

Round, flatted

**Actuator Type:**

Single shaft

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Rear end

**Mounting Method:**

Standard bushing

**Electrical Resistance Per Section:**

3.0 percent, rated amperes c and better

**Power Dissipation Rating Per Section In Watts:**

12.5 7th secondary at 10'30 oclock

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 all sections

**Special Features:**

Resistors mechanically connected in tandem bracket has nonturn device in 6 o'clock position with a radius of 0.500 in.

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0