## NSN 5905-01-195-0923

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-195-0923

| Section Quantity:   |
|---|
| 1   |
| Body Style:   |
| Rectangular   |
| Reliability Indicator:  |
| Not established   |
| Body Length:  |
| 0.250 inches  |
| Body Width:   |
| 0.400 inches  |
| Body Height:  |
| 0.400 inches  |
| Actuator Type:  |
| Flush drive with slot-hole  |
| Effective Electrical Rotation In Deg Angular Rotation:                      |
| 280.0   |
| Maximum Starting Torque:  |
| 5.00 inch-ounces  |
| Terminal Location:  |
| Rear end  |
| Mounting Method:  |
| Terminal  |
| Features Provided:  |
| Humidity proof  |
| Electrical Resistance Per Section:  |
| 500.000 percent, rated amperes c and better flooring                        |
| Rotary Actuator Travel In Angular Deg:                                      |
| 310.0   |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 125.0 single section  |
| Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:   |
| -100.0/+100.0 single section  |
| Power Dissipation Rating Per Section In Watts:                              |
| 0.5 7th secondary quality   |
| Resistance Tolerance Per Section In Percent:                                |
| -10.0/+10.0 single section  |
| Actuator Travel Control Feature:  |
| Stops   |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:         |
| 70.0 single section   |
| Standard Taper Curve Per Section:   |
| A single section  |

## NSN 5905-01-195-0923

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



| Terminal Type And Quantity: |
|-----------------------------|
| 3 tab, solder lug           |
| Shelf Life:                 |
| N/a                         |
| Unit Of Measure:            |
|                             |
| Demilitarization:           |
| No                          |
| Fiig:                       |

A002a0