NSN 5905-01-195-5511

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-195-5511

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
Between 1.095 inches and 1.155 inches
Body Diameter:
Between 0.609 inches and 0.635 inches
Shaft Diameter:
Between 0.235 inches and 0.265 inches
Shaft Length:
Between 0.735 inches and 0.765 inches
Mounting Bushing Length:
Between 0.234 inches and 0.266 inches
Body Length:
Between 0.360 inches and 0.390 inches
Overall Diameter:
Between 0.609 inches and 0.635 inches
Shaft Style:
Round
Shaft Bearing Type:
Sleeve
Actuator Type:
Single shaft
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
1.0 kilohms single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
0.250 free air single section

NSN 5905-01-195-5511

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



-30.0/+30.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0