

View Online at <https://aerobasegroup.com/nsn/5905-01-195-5513>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

Between 0.609 inches and 0.639 inches

Shaft Diameter:

Between 0.235 inches and 0.265 inches

Shaft Length:

Between 0.735 inches and 0.765 inches

Mounting Bushing Length:

0.250 inches

Body Length:

Between 0.360 inches and 0.390 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

50.0 kilohms single section

Power Dissipation Rating Per Section In Watts:

0.25 free air single section

Resistance Tolerance Per Section In Percent:

-30.0/+30.0 single section

Criticality Code Justification:

Feat

Standard Taper Curve Per Section:

A single section

Special Features:

90 percent change in total resistance for a 50 percent clockwise rotation, low end hopoffs of 1000 ohms

Terminal Type And Quantity:

3 tab, solder lug

Specification Data:

98230-0n312812 manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0