

View Online at <https://aerobasegroup.com/nsn/5905-01-195-5513>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Body Diameter:**

Between 0.609 inches and 0.639 inches

**Shaft Diameter:**

Between 0.235 inches and 0.265 inches

**Shaft Length:**

Between 0.735 inches and 0.765 inches

**Mounting Bushing Length:**

0.250 inches

**Body Length:**

Between 0.360 inches and 0.390 inches

**Shaft Style:**

Round

**Actuator Type:**

Single shaft

**Screw Thread Diameter:**

0.250 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Standard bushing

**Electrical Resistance Per Section:**

50.0 kilohms single section

**Power Dissipation Rating Per Section In Watts:**

0.25 free air single section

**Resistance Tolerance Per Section In Percent:**

-30.0/+30.0 single section

**Criticality Code Justification:**

Feat

**Standard Taper Curve Per Section:**

A single section

**Special Features:**

90 percent change in total resistance for a 50 percent clockwise rotation, low end hopoffs of 1000 ohms

**Terminal Type And Quantity:**

3 tab, solder lug

**Specification Data:**

98230-0n312812 manufacturers specification control

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0