

View Online at <https://aerobasegroup.com/nsn/5905-01-195-9570>

**Section Quantity:**

1

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

0.7500 inches

**Pilot Length:**

0.0620 inches

**Overall Length:**

1.200 inches

**Undercut Diameter:**

0.781 inches

**Undercut Width:**

0.0570 inches

**Body Diameter:**

0.875 inches

**Shaft Diameter:**

0.1248 inches

**Shaft Length:**

0.500 inches

**Body Length:**

0.700 inches

**Overall Diameter:**

1.250 inches

**Mounting Lip Diameter:**

0.8750 inches

**Mounting Lip Depth:**

0.0620 inches

**Shaft Style:**

Round

**Shaft Bearing Type:**

Ball

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

180.0

**Maximum Starting Torque:**

0.50 inch-ounces

**Maximum Running Torque:**

0.20 inch-ounces

**Shaft End Play:**

0.00500 inches

**Shaft Runout:**

0.0015 inches

**Lateral Runout:**

0.003 inches

**Pilot Diameter Runout:**

0.00200 inches

**Shaft Radial Play:**

0.0025 inches

**Fragility Factor:**

Moderately rugged

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Clamp ring

**Features Provided:**

Pressure mounted tap

**Electrical Resistance Per Section:**

10.000 percent, rated amperes c and better flooring

**Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:**

90.0 single section

**Rotary Actuator Travel In Angular Deg:**

360.0

**Function Conformity Tolerance Per Section:**

-0.30/+0.30 single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

85.0 single section

**Power Dissipation Rating Per Section In Watts:**

0.75 7th secondary quality

**Function Conformity Per Section:**

Single section independent linearity

**Fixed Tap Quantity Per Section:**

1 single section

**Tap Location Tolerance Per Section:**

-0.5/+0.5 degrees angular rotation single section

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

**Actuator Travel Control Feature:**

Continuous motion

**Function Characteristic Per Section:**

7 oclock all primaries

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

40.0 single section

**Terminal Type And Quantity:**

4 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0