NSN 5905-01-196-5082

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-196-5082 **Section Quantity: Body Style:** Rectangular **Reliability Indicator:** Not established **Overall Length:** 0.465 inches **Terminal Length:** 0.200 inches **Overall Height:** 0.250 inches **Overall Width:** 0.165 inches **Shaft Diameter:** 0.065 inches **Shaft Length:** 0.040 inches **Body Length:** 0.250 inches **Body Width:** 0.165 inches **Body Height:** 0.250 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 4320.0 **Maximum Starting Torque:** 3.00 inch-ounces **Maximum Running Torque:** 3.00 inch-ounces **Center To Center Distance Between Terminals:**

0.200 inches **Fragility Factor:** Moderately rugged **Terminal Location:** Rear end **Mounting Method:** Terminal

NSN 5905-01-196-5082

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Features Provided:
Humidity proof
Electrical Resistance Per Section:
500.0 ohms c and better flooring
Rotary Actuator Travel In Angular Deg:
4320.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0/+100.0 single section
Power Dissipation Rating Per Section In Watts:
0.25 7th secondary quality
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0