NSN 5905-01-197-4635

-200.0/+200.0

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-197-4635

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

120.000 ohms Resistance Tolerance in Percent: -2.000/+2.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 125.0 Ambient Tempurature Range Of Tempurature Coefficient in Deg Celsius: -65.00/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 8 Terminal Quantity: 8 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: 0.125 inches Body Length: 0.780 inches Body Width: 0.090 inches Body Width: 0.190 inches Body Height: 0.190 inches Body Height: 0.190 inches Body Height: 0.190 inches Chematic Diagram Designator: Isolated array Power Dissipation Rating in Watts: 0.720 total network Identical Value Resistor Quantity: 4 each resistor Style Designator: Single inline	Electrical Resistance:
-2.000/+2.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 8 Terminal Quantity: 8 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: 0.125 inches Body Length: 0.780 inches Body Width: 0.090 inches Body Width: 0.190 inches Body Height: 0.190 inches Body Height: 0.190 inches Body Length: 0.790 inches Body Height: 0.190 inches Body	120.000 ohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 8 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: 0.125 inches Body Length: 0.780 inches Body Width: 0.090 inches Body Width: 0.190 inches Body Height: 0.190 inches Body Height: 0.750 inches Body Length:	Resistance Tolerance In Percent:
25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 8 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: 0.125 inches Body Length: 0.780 inches Body Width: 0.090 inches Body Width: 0.190 inches Body Height: 0.190 inches Schematic Diagram Designator: Isolated array Power Dissipation Rating In Watts: 0.720 total network dentical Value Resistor Quantity: 4 each resistor Style Designator: Single inline Test Data Document:	-2.000/+2.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 8 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: 0.125 inches Body Length: 0.780 inches Body Wieth: 0.090 inches Body Height: 0.190 inches Schematic Diagram Designator: Isolated array Power Dissipation Rating In Watts: 0.720 total network dientical Value Resistor Quantity: 4 each resistor Stiple inline Test Data Document:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 8 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: 0.125 inches Body Length: 0.780 inches Body Width: 0.090 inches Body Height: 0.190 inches Schematic Diagram Designator: Isolated array Power Dissipation Rating In Watts: 0.720 total network Identical Value Resistor Quantity: 4 each resistor Style Designator: Single inline Test Data Document:	25.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -65.0/+125.0 Inclosure Method: Encapsulated Terminal Quantity: 8 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: 0.125 inches Body Length: 0.780 inches Body Width: 0.090 inches Body Height: 0.190 inches Schematic Diagram Designator: Isolated array Power Dissipation Rating In Watts: 0.720 total network Identical Value Resistor Quantity: 4 each resistor Style Designator: Single inline Single inline Test Data Document:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
inclosure Method: Encapsulated Terminal Quantity: 8 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: 0.125 inches Body Length: 0.780 inches Body Width: 0.090 inches Body Height: 0.190 inches Body Height: 0.190 inches Body Height: 0.190 inches Body Height: 0.190 inches Cohematic Diagram Designator: Isolated array Power Dissipation Rating In Watts: 0.720 total network Identical Value Resistor Quantity: 4 each resistor Style Designator: Single inline Test Data Document:	125.0
Inclosure Method: Encapsulated Terminal Quantity: 8 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: 0.125 inches Body Length: 0.780 inches Body Width: 0.090 inches Body Height: 0.190 inches Schematic Diagram Designator: Isolated array Power Dissipation Rating In Watts: 0.720 total network Identical Value Resistor Quantity: 4 each resistor Style Designator: Single inline Test Data Document:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Quantity: 8 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: 0.125 inches Body Length: 0.780 inches Body Width: 0.090 inches Body Height: 0.190 inches Schematic Diagram Designator: Isolated array Power Dissipation Rating In Watts: 0.720 total network Identical Value Resistor Quantity: 4 each resistor Style Designator: Single inline Test Data Document:	-65.0/+125.0
Terminal Quantity: 8 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: 0.125 inches Body Length: 0.780 inches Body Width: 0.090 inches Body Height: 0.190 inches Schematic Diagram Designator: Isolated array Power Dissipation Rating In Watts: 0.720 total network Identical Value Resistor Quantity: 4 each resistor Style Designator: Single inline Test Data Document:	Inclosure Method:
8 Terminal Type: Pin Reliability Indicator: Not established Terminal Length: 0.125 inches Body Length: 0.780 inches Body Width: 0.090 inches Body Height: 0.190 inches Schematic Diagram Designator: Isolated array Power Dissipation Rating In Watts: 0.720 total network Identical Value Resistor Quantity: 4 each resistor Style Designator: Single inline Test Data Document:	Encapsulated
Terminal Type: Pin Reliability Indicator: Not established Terminal Length: 0.125 inches Body Length: 0.780 inches Body Width: 0.090 inches Body Height: 0.190 inches Schematic Diagram Designator: Isolated array Power Dissipation Rating In Watts: 0.720 total network Identical Value Resistor Quantity: 4 each resistor Style Designator: Single inline Test Data Document:	Terminal Quantity:
Pin Reliability Indicator: Not established Terminal Length: 0.125 inches Body Length: 0.780 inches Body Width: 0.090 inches Body Height: 0.190 inches Schematic Diagram Designator: Isolated array Power Dissipation Rating In Watts: 0.720 total network Identical Value Resistor Quantity: 4 each resistor Style Designator: Single inline Test Data Document:	8
Reliability Indicator: Not established Terminal Length: 0.125 inches Body Length: 0.780 inches Body Width: 0.090 inches Body Height: 0.190 inches Schematic Diagram Designator: Isolated array Power Dissipation Rating In Watts: 0.720 total network Identical Value Resistor Quantity: 4 each resistor Style Designator: Single inline Test Data Document:	Terminal Type:
Not established Terminal Length: 0.125 inches Body Length: 0.780 inches Body Width: 0.090 inches Body Height: 0.190 inches Schematic Diagram Designator: Isolated array Power Dissipation Rating In Watts: 0.720 total network Identical Value Resistor Quantity: 4 each resistor Style Designator: Single inline Test Data Document:	Pin
Terminal Length: 0.125 inches Body Length: 0.780 inches Body Width: 0.090 inches Body Height: 0.190 inches Schematic Diagram Designator: Isolated array Power Dissipation Rating In Watts: 0.720 total network Identical Value Resistor Quantity: 4 each resistor Style Designator: Single inline Test Data Document:	Reliability Indicator:
0.125 inches Body Length: 0.780 inches Body Width: 0.090 inches Body Height: 0.190 inches Schematic Diagram Designator: Isolated array Power Dissipation Rating In Watts: 0.720 total network Identical Value Resistor Quantity: 4 each resistor Style Designator: Single inline Test Data Document:	Not established
Body Length: 0.780 inches Body Width: 0.090 inches Body Height: 0.190 inches Schematic Diagram Designator: Isolated array Power Dissipation Rating In Watts: 0.720 total network Identical Value Resistor Quantity: 4 each resistor Style Designator: Single inline Test Data Document:	Terminal Length:
0.780 inches Body Width: 0.090 inches Body Height: 0.190 inches Schematic Diagram Designator: Isolated array Power Dissipation Rating In Watts: 0.720 total network Identical Value Resistor Quantity: 4 each resistor Style Designator: Single inline Test Data Document:	0.125 inches
Body Width: 0.090 inches Body Height: 0.190 inches Schematic Diagram Designator: Isolated array Power Dissipation Rating In Watts: 0.720 total network Identical Value Resistor Quantity: 4 each resistor Style Designator: Single inline Test Data Document:	Body Length:
0.090 inches Body Height: 0.190 inches Schematic Diagram Designator: Isolated array Power Dissipation Rating In Watts: 0.720 total network Identical Value Resistor Quantity: 4 each resistor Style Designator: Single inline Test Data Document:	0.780 inches
Body Height: 0.190 inches Schematic Diagram Designator: Isolated array Power Dissipation Rating In Watts: 0.720 total network Identical Value Resistor Quantity: 4 each resistor Style Designator: Single inline Test Data Document:	Body Width:
0.190 inches Schematic Diagram Designator: Isolated array Power Dissipation Rating In Watts: 0.720 total network Identical Value Resistor Quantity: 4 each resistor Style Designator: Single inline Test Data Document:	0.090 inches
Schematic Diagram Designator: Isolated array Power Dissipation Rating In Watts: 0.720 total network Identical Value Resistor Quantity: 4 each resistor Style Designator: Single inline Test Data Document:	Body Height:
Isolated array Power Dissipation Rating In Watts: 0.720 total network Identical Value Resistor Quantity: 4 each resistor Style Designator: Single inline Test Data Document:	0.190 inches
Power Dissipation Rating In Watts: 0.720 total network Identical Value Resistor Quantity: 4 each resistor Style Designator: Single inline Test Data Document:	Schematic Diagram Designator:
0.720 total network Identical Value Resistor Quantity: 4 each resistor Style Designator: Single inline Test Data Document:	Isolated array
Identical Value Resistor Quantity: 4 each resistor Style Designator: Single inline Test Data Document:	Power Dissipation Rating In Watts:
4 each resistor Style Designator: Single inline Test Data Document:	0.720 total network
Style Designator: Single inline Test Data Document:	Identical Value Resistor Quantity:
Single inline Test Data Document:	4 each resistor
Test Data Document:	Style Designator:
	Single inline
	Test Data Document:
15280-43-055216 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,	15280-43-055216 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)	etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:	Shelf Life:
N/a	N/a
	Unit Of Measure:
	Unit Of Measure:

NSN 5905-01-197-4635

Film Fixed Resistor Network - Page 2 of 2



Demilitarization:

No

Fiig:

A001a0