

View Online at <https://aerobasegroup.com/nsn/5905-01-197-6560>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

2.000 inches

Shaft Diameter:

Between 0.2494 inches and 0.2497 inches

Shaft Length:

0.875 inches

Mounting Bushing Length:

0.375 inches

Body Length:

0.905 inches

Shaft Style:

Round

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Maximum Starting Torque:

1.50 inch-ounces

Maximum Running Torque:

1.10 inch-ounces

Nonturn Device Location:

At 6 oclock

Nonturn Device Radius:

0.531 inches

Shaft End Play:

0.50000 inches

Shaft Runout:

0.0005 inches

Lateral Runout:

0.004 inches

Pilot Diameter Runout:

0.00200 inches

Shaft Radial Play:

0.004 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

2.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-0.50/+0.50 single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Power Dissipation Rating Per Section In Watts:

3.5 free air single section

Function Conformity Per Section:

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

Single section linear

Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-130.0/+130.0 single section

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0