Nonprecision Wire Wound Variable Resistor - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5905-01-199-1115

# Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

# **Body Diameter:**

1.590 inches

#### Shaft Diameter:

0.250 inches

Shaft Length:

0.875 inches

# Mounting Bushing Length:

0.375 inches

Body Length:

# 0.620 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

# Effective Electrical Rotation In Deg Angular Rotation:

Between 280.0 and 305.0

# Maximum Starting Torque:

6.00 inch-ounces

# Maximum Running Torque:

6.00 inch-ounces

# Maximum Stop Torque:

128.00 inch-ounces

# Nonturn Device Location:

At 9 oclock

# Nonturn Device Radius:

0.531 inches

# **Fragility Factor:**

Rugged

# Screw Thread Diameter:

0.375 inches

# Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference



### **Mounting Method:**

Standard bushing w/panel seal and standard bushing w/shaft seal

### **Electrical Resistance Per Section:**

150.0 ohms single section

**Rotary Actuator Travel In Angular Deg:** 

Between 280.0 and 305.0

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

**Power Dissipation Rating Per Section In Watts:** 

4.0 free air single section

**Resistance Tolerance Per Section In Percent:** 

-10.0/+10.0 single section

Actuator Travel Control Feature:

Stops

#### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

#### **Test Data Document:**

81349-mil-r-19 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 

3 tab, solder lug

**Specification Data:** 

81349-mil-r-19/3 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0