## NSN 5905-01-199-3756

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-199-3756

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
1.156 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.859 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.625 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
292.0
Maximum Running Torque:
6.00 inch-ounces
Maximum Stop Torque:
192.00 inch-ounces
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.531 inches
Mechanical Backlash In Deg Angular Rotation:
1.5
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
32.0
Mounting Method:
<del></del> -
Mounting Method:

## NSN 5905-01-199-3756

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:
333.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
2.25 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
<del>-</del>
Demilitarization:
No