NSN 5905-01-199-9019

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-199-9019 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.375 inches **Body Diameter:** 0.625 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.750 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.625 inches **Overall Diameter:** 1.124 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Sleeve Switch Type: Rotary **Switch Voltage Rating In Volts:** 125.0 **Contact Arm Electrical Off Position:** Fully ccw **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 270.0 **Maximum Starting Torque:**

27.00 inch-ounces

Maximum Running Torque:
6.00 inch-ounces

Maximum Stop Torque:
96.00 inch-ounces

Nonturn Device Location:

At 9 oclock

NSN 5905-01-199-9019

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 3



Nonturn Device Radius:
0.312 inches
Switch Operating Position:
Start of rotation
Switch Contact Arrangement:
Single pole, single throw, normally open, both positions maintained
Fragility Factor:
Moderately rugged
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear-bottom
Mounting Method:
Standard bushing
Features Provided:
Humidity proof and switch
Cubic Measure:
0.225 cubic inches
Electrical Resistance Per Section:
5.000 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:
325.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-150.0/+300.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 7th secondary quality
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Switch Current Type And Rating In Amps:
1.000 ac/dc
Standard Taper Curve Per Section:

5 tab, solder lug

A single section

Terminal Type And Quantity:

NSN 5905-01-199-9019

Nonprecision Nonwire Wound Variable Resistor - Page 3 of 3



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0