## NSN 5905-01-199-9445

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-199-9445

Section Quantity:
1
Body Style:
Rectangular w/mounting holes/slots
Terminal Length:
0.500 inches
Overall Height:
0.110 inches
Mounting Hole Diameter:
0.093 inches
Shaft Length:
0.070 inches
Body Length:
1.250 inches
Body Width:
0.190 inches
Body Height:
0.315 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Maximum Starting Torque:
5.00 inch-ounces
Maximum Running Torque:
5.00 inch-ounces
Center To Center Distance Between Terminals:
0.900 inches
Lateral Distance Between Mounting Hole Centers:
1.000 inches
Mounting Facility Quantity:
2
Terminal Location:
Lower adjacent side single row
Mounting Method:
Unthreaded hole
Electrical Resistance Per Section:
1.000 kilohms single section
Center To Center Distance Between Center Terminal And Outside Terminal:
0.700 inches
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100 0/+100 0 single section

## NSN 5905-01-199-9445

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A002a0