

View Online at <https://aerobasegroup.com/nsn/5905-01-200-1391>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Shaft Style:**

Round, slotted

**Switch Type:**

Sensitive

**Switch Voltage Rating In Volts:**

28.0

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

90.0

**Switch Operating Position:**

Start of rotation

**Switch Contact Arrangement:**

Single pole, double throw, three positions maintained

**Fragility Factor:**

Moderately rugged

**Terminal Location:**

Rear end

**Mounting Method:**

Bracket and standard bushing

**Features Provided:**

Switch

**Electrical Resistance Per Section:**

15.1 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

90.0

**Resistance Tolerance Per Section In Percent:**

-3.0/+3.0 single section

**Actuator Travel Control Feature:**

Stops

**Switch Current Type And Rating In Amps:**

8.000 dc

**Standard Taper Curve Per Section:**

A single section

**Precious Material And Location:**

Switch contacts silver

**Precious Material:**

Silver

**Terminal Type And Quantity:**

7 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0