NSN 5905-01-200-3056

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-200-3056

-50.0/+50.0 Electrical Resistance: 1.6.000 kish.ms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 176.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 176.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: N/a Unit of Measure: Demilitarization: No Figis A001a0	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
16.900 kilohms Resistance Tolerance in Percent: -1.000/41.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 77.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 175.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level in Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating in Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil+r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Sheff Life: N/a Unit Of Measure:	-50.0/+50.0
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Dlameter: 0.109 inches Body Dlameter: 0.109 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-mill-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Na Unit Of Measure:	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	16.900 kilohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-mill-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	-1.000/+1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr-55182 specification (includes engineering type builletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-mill-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	70.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level in Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-mill-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	175.0
Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 Inches Body Length: 0.250 Inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-mill-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Inclosure Method:
Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Encapsulated
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Terminal Type:
Established Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fitig:	Wire lead
Reliability Failure Rate Level In Percent: 0.001 Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Reliability Indicator:
Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Established
Body Diameter: 0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Reliability Failure Rate Level In Percent:
0.109 inches Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.001
Body Length: 0.250 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Diameter:
O.250 inches Power Dissipation Rating In Watts: O.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.109 inches
Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fitig:	Body Length:
O.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.250 inches
Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
Axial terminal each end Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.125 free air
Test Data Document: 81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal each end
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
N/a Unit Of Measure: Demilitarization: No Fiig:	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0