NSN 5905-01-200-4882

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-200-4882

Section Quantity:
1
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
0.9688 inches
Pilot Length:
0.0620 inches
Undercut Diameter:
0.975 inches
Undercut Width:
0.0620 inches
Body Diameter:
1.062 inches
Shaft Diameter:
0.1248 inches
Shaft Length:
0.500 inches
Body Length:
0.747 inches
Mounting Lip Diameter:
1.0620 inches
Mounting Lip Depth:
0.0620 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Shaft Radial Play:
0.002 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
20.000 kilohms single section
Power Dissipation Rating Per Section In Watts:
0.75 free air single section
Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

NSN 5905-01-200-4882

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0