NSN 5905-01-201-4391

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-201-4391

Ocation Oceanities
Section Quantity:
1 Podu Stulov
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
1.875 inches
Body Diameter:
1.156 centimeters
Shaft Diameter:
0.250 inches
Shaft Length:
0.875 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.812 inches
Overall Diameter:
1.750 inches
Shaft Style:
Round
Shaft Bearing Type:
Sleeve
Switch Type:
Rotary
Switch Voltage Rating In Volts:
125.0
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
292.0
Maximum Starting Torque:
9.00 inch-ounces
Maximum Running Torque:
9.00 inch-ounces
Maximum Stop Torque:
192.00 inch-ounces
Switch Operating Position:
Start of rotation
Switch Contact Arrangement:

Owner Contact Arrangement.

Single pole, single throw, normally open, both positions maintained

NSN 5905-01-201-4391

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 3



Fragility Factor:
Moderately rugged
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Jnef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear-bottom
Mounting Method:
Standard bushing
Features Provided:
Switch
Cubic Measure:
0.818 cubic inches
Electrical Resistance Per Section:
1.000 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:
333.0
Resistance Tempurature Characteristic Range Per Section In Percent:
+0.0/+5.5 -55 degrees celsius single section and +0.0/+3.0 -25 degrees celsius single section and +0.0/+1.5 0 degrees celsius single section
and -2.0/+2.0 85 degrees celsius single section and +0.0/+4.5 120 degrees celsius single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
2.25 7th secondary quality
Resistance Tolerance Per Section In Percent:
10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Switch Current Type And Rating In Amps:
2.000 ac
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
5 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

No

Demilitarization:

NSN 5905-01-201-4391

Nonprecision Nonwire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0