## NSN 5905-01-201-6584

Thermal Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-201-6584

view Online at https://aerobasegroup.com/hsh/0300-01-201-0004
Reliability Indicator:
Not established
Terminal Length:
1.200 inches
Body Length:
0.285 inches
Body Outside Diameter:
0.100 inches
Terminal Diameter:
0.020 inches
Maximum Power Dissipation Rating:
250.00 milliwatts
Ambient Tempurature At Full Rated Power:
25.0 degrees celsius
Maximum Operating Temp:
125.0 degrees celsius
Thermal Time Constant In Seconds:
60.0
Power Dissipation Constant In Milliwatts Per Deg Celsius:
2.5
Zero Power Tempurature Coefficient Of Resistance In Percent Per Deg Celsius:
0.55
Tempurature Points For Resistance Readings At Zero Power:
75.0 degrees celsius 4th resistance-temperature point
Zero Power Resistance At Specificationified Temp:
2.6 kilohms 1st resistance-temperature point
Resistance Tolerance At A Specificationified Tempurature In Percent:
-9.0/+9.0 4th resistance-temperature point
Inclosure Type:
Hermetically sealed
Cubic Measure:
0.002 cubic inches
Zero Power Resistance:
5.100 kilohms
Zero Power Resistance Tolerance In Percent At Reference Temp:
-5.0/+5.0
Reference Tempurature In Deg Celsius:
25.0
Style Designator:
Rod
Test Data Document:
81349-mil-r-23648 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

81349-mil-r-23648 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## NSN 5905-01-201-6584

Thermal Resistor - Page 2 of 2



Terminal Type And Quantity:
2 wire lead
Specification Data:
81349-mil-r-23648/19 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A086a0