## NSN 5905-01-202-8292

Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-202-8292

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:						
-100.0/+100.0						
Electrical Resistance:						
0.210 ohms						
Resistance Tolerance In Percent:						
-1.000/+1.000						
Ambient Tempurature In Deg Celsius At Full Rated Power:						
25.0						
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:						
275.0						
Tempurature Range Of Tempurature Coefficient In Deg Celsius:						
-55.0/+275.0						
Inclosure Method:						
Encased						
Terminal Type:						
Tab, solder lug						
Reactance Characteristic:						
Inductive						
Reliability Indicator:						
Established						
Reliability Failure Rate Level In Percent:						
0.010						
Terminal Length:						
0.312 inches						
Body Length:						
0.750 inches						
Body Width:						
0.438 inches						
Body Height:						
0.406 inches						
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:						
0.562 inches						
0.562 inches  Power Dissipation Rating In Watts:						
Power Dissipation Rating In Watts:						
Power Dissipation Rating In Watts: 6.000 free air						
Power Dissipation Rating In Watts: 6.000 free air Terminal Width:						
Power Dissipation Rating In Watts: 6.000 free air Terminal Width: 0.140 inches						
Power Dissipation Rating In Watts: 6.000 free air Terminal Width: 0.140 inches Mounting Hole Size:						
Power Dissipation Rating In Watts: 6.000 free air Terminal Width: 0.140 inches Mounting Hole Size: 0.094 inches						

8.000 grams

## NSN 5905-01-202-8292

Wire Wound Fixed Resistor - Page 2 of 2



<b>~</b> ·			•		
Styl	ΔІ	100	เตท	ato	ŀ۲۰
Oty:		,,,	.9	ato	

Axial terminal (s)

## **Test Data Document:**

81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-r-39009/1 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A001a0