NSN 5905-01-203-3870

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-203-3870

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: -50.0/+50.0 Electrical Resistance: 332.000 kilohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.092 inches and 0.102 inches Body Length: Between 0.250 inches and 0.270 inches Power Dissipation Rating In Watts: 0.100 free air Terminal Width: 0.025 inches Style Designator: Axial terminal each end
Electrical Resistance: 332.000 kilohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.092 inches and 0.102 inches Body Length: Between 0.250 inches and 0.270 inches Power Dissipation Rating In Watts: 0.100 free air Terminal Width: 0.025 inches Style Designator:
332.000 kilohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.092 inches and 0.102 inches Body Length: Between 0.250 inches and 0.270 inches Power Dissipation Rating In Watts: 0.100 free air Terminal Width: 0.025 inches Style Designator:
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.092 inches and 0.102 inches Body Length: Between 0.250 inches and 0.270 inches Power Dissipation Rating In Watts: 0.100 free air Terminal Width: 0.025 inches Style Designator:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.092 inches and 0.102 inches Body Length: Between 0.250 inches and 0.270 inches Power Dissipation Rating In Watts: 0.100 free air Terminal Width: 0.025 inches Style Designator:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.092 inches and 0.102 inches Body Length: Between 0.250 inches and 0.270 inches Power Dissipation Rating In Watts: 0.100 free air Terminal Width: 0.025 inches Style Designator:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.092 inches and 0.102 inches Body Length: Between 0.250 inches and 0.270 inches Power Dissipation Rating In Watts: 0.100 free air Terminal Width: 0.025 inches Style Designator:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.092 inches and 0.102 inches Body Length: Between 0.250 inches and 0.270 inches Power Dissipation Rating In Watts: 0.100 free air Terminal Width: 0.025 inches Style Designator:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.092 inches and 0.102 inches Body Length: Between 0.250 inches and 0.270 inches Power Dissipation Rating In Watts: 0.100 free air Terminal Width: 0.025 inches Style Designator:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.092 inches and 0.102 inches Body Length: Between 0.250 inches and 0.270 inches Power Dissipation Rating In Watts: 0.100 free air Terminal Width: 0.025 inches Style Designator:
-55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.092 inches and 0.102 inches Body Length: Between 0.250 inches and 0.270 inches Power Dissipation Rating In Watts: 0.100 free air Terminal Width: 0.025 inches Style Designator:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.092 inches and 0.102 inches Body Length: Between 0.250 inches and 0.270 inches Power Dissipation Rating In Watts: 0.100 free air Terminal Width: 0.025 inches Style Designator:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.092 inches and 0.102 inches Body Length: Between 0.250 inches and 0.270 inches Power Dissipation Rating In Watts: 0.100 free air Terminal Width: 0.025 inches Style Designator:
Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.092 inches and 0.102 inches Body Length: Between 0.250 inches and 0.270 inches Power Dissipation Rating In Watts: 0.100 free air Terminal Width: 0.025 inches Style Designator:
Wire lead Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.092 inches and 0.102 inches Body Length: Between 0.250 inches and 0.270 inches Power Dissipation Rating In Watts: 0.100 free air Terminal Width: 0.025 inches Style Designator:
Reliability Indicator: Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.092 inches and 0.102 inches Body Length: Between 0.250 inches and 0.270 inches Power Dissipation Rating In Watts: 0.100 free air Terminal Width: 0.025 inches Style Designator:
Not established Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.092 inches and 0.102 inches Body Length: Between 0.250 inches and 0.270 inches Power Dissipation Rating In Watts: 0.100 free air Terminal Width: 0.025 inches Style Designator:
Terminal Length: Between 1.375 inches and 1.625 inches Body Diameter: Between 0.092 inches and 0.102 inches Body Length: Between 0.250 inches and 0.270 inches Power Dissipation Rating In Watts: 0.100 free air Terminal Width: 0.025 inches Style Designator:
Between 1.375 inches and 1.625 inches Body Diameter: Between 0.092 inches and 0.102 inches Body Length: Between 0.250 inches and 0.270 inches Power Dissipation Rating In Watts: 0.100 free air Terminal Width: 0.025 inches Style Designator:
Body Diameter: Between 0.092 inches and 0.102 inches Body Length: Between 0.250 inches and 0.270 inches Power Dissipation Rating In Watts: 0.100 free air Terminal Width: 0.025 inches Style Designator:
Between 0.092 inches and 0.102 inches Body Length: Between 0.250 inches and 0.270 inches Power Dissipation Rating In Watts: 0.100 free air Terminal Width: 0.025 inches Style Designator:
Body Length: Between 0.250 inches and 0.270 inches Power Dissipation Rating In Watts: 0.100 free air Terminal Width: 0.025 inches Style Designator:
Between 0.250 inches and 0.270 inches Power Dissipation Rating In Watts: 0.100 free air Terminal Width: 0.025 inches Style Designator:
Power Dissipation Rating In Watts: 0.100 free air Terminal Width: 0.025 inches Style Designator:
0.100 free air Terminal Width: 0.025 inches Style Designator:
Terminal Width: 0.025 inches Style Designator:
0.025 inches Style Designator:
Style Designator:
Axial terminal each end
Shelf Life:
N/a
Unit Of Measure:
Unit Of Measure:
Unit Of Measure: Demilitarization:
Demilitarization:
Demilitarization: