NSN 5905-01-203-5758

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-203-5758 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.078 inches **Body Diameter:** 1.312 inches **Shaft Diameter:** 0.2497 inches **Shaft Length:** 1.187 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.734 inches **Overall Diameter:** 1.343 inches **Shaft Style:** Round **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 350.0 **Maximum Starting Torque:** 1.00 inch-ounces **Maximum Running Torque:** 0.70 inch-ounces **Maximum Stop Torque:** 48.00 inch-ounces **Nonturn Device Location:** At 6 oclock **Nonturn Device Radius:** 0.562 inches **Shaft End Play:** 0.007 inches

Shaft Runout: 0.0025 inches

NSN 5905-01-203-5758

Lateral Runout:

Precision Wire Wound Variable Resistor - Page 2 of 3



0.003 inches
Pilot Diameter Runout:
0.0025 inches
Shaft Radial Play:
0.004 inches
Fragility Factor:
Moderately rugged
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear end
Mounting Method:
Standard bushing
Features Provided:
Humidity proof
Cubic Measure:
1.100 cubic inches
Electrical Resistance Per Section:
1.0 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:
350.0
Function Conformity Tolerance Per Section:
-0.50/+0.50 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 7th secondary quality
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-3.0/+3.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
7 oclock all primaries
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
3 turret

NSN 5905-01-203-5758

Precision Wire Wound Variable Resistor - Page 3 of 3



Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0