

View Online at <https://aerobasegroup.com/nsn/5905-01-204-4676>

Section Quantity:

1

Body Style:

Cylindrical

Reliability Indicator:

Not established

Terminal Length:

0.177 inches

Body Diameter:

0.268 inches

Body Length:

0.200 inches

Shaft Bearing Type:

Sleeve

Actuator Type:

Flush drive with slot-hole

Effective Electrical Rotation In Deg Angular Rotation:

200.0

Maximum Starting Torque:

250.00 centimeter-grams

Maximum Running Torque:

250.00 centimeter-grams

Maximum Stop Torque:

300.00 centimeter-grams

Center To Center Distance Between Terminals:

0.197 inches

Fragility Factor:

Moderately rugged

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Terminal

Features Provided:

Humidity proof

Cubic Measure:

0.013 cubic inches

Electrical Resistance Per Section:

100.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

200.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.098 inches

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

100.0 single section

Power Dissipation Rating Per Section In Watts:

0.3 free air single section

Resistance Tolerance Per Section In Percent:

-20.0/+20.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

50.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0