## NSN 5905-01-206-2152

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-206-2152

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-100.0/+100.0 first temp coefficient
Electrical Resistance:
1.000 kilohms
Resistance Tolerance In Percent:
-2.000/+2.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
25.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
150.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-65.0/+150.0
Inclosure Method:
Hermetically sealed
Terminal Quantity:
8
Terminal Type:
Tab, solder lug
Reliability Indicator:
Not established
Terminal Length:
Between 0.170 inches and 0.195 inches
Body Length:
0.790 inches
Body Width:
0.090 inches
Body Height:
0.200 inches
Schematic Diagram Designator:
Ladder network
Power Dissipation Rating In Watts:
0.950 total network
Terminal Width:
Between 0.008 inches and 0.016 inches
End Application:
Sh-60b helicopter
Identical Value Resistor Quantity:
7 each resistor
Style Designator:
Single inline
Test Data Document:

86360-530c6000-02 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

## NSN 5905-01-206-2152

Film Fixed Resistor Network - Page 2 of 2



	Sı	peci	fica	tion	Data
--	----	------	------	------	------

86360-530c6000-02 manufacturers source control

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A001a0