NSN 5905-01-207-2420

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-207-2420

viou crimine at maps, , acrossacogre	apissii#iisi#6666 61 261 2 126
Section Quantity:	
1	
Body Style:	
Rectangular	
Reliability Indicator:	
Not established	
Terminal Length:	
Between 0.173 inches and 0.203 in	nches
Shaft Diameter:	
0.070 inches	
Shaft Length:	
Between 0.025 inches and 0.045 in	nches
Body Length:	
Between 0.230 inches and 0.270 in	nches
Body Width:	
Between 0.025 inches and 0.055 in	nches
Body Height:	
Between 0.230 inches and 0.270 in	nches
Shaft Style:	
Round, slotted	
Actuator Type:	
Single shaft	
Center To Center Distance Between	een Terminals:
0.100 inches	
Terminal Location:	
Rear end	
Mounting Method:	
Printed circuit	
Electrical Resistance Per Section	n:
50.000 ohms single section	
Center To Center Distance Between	een Center Terminal And Outside Terminal:
0.100 inches	
Ambient Tempurature In Deg Ce	Isius Per Section At Zero Percent Rated Power:
150.0 single section	
Tempurature Coefficient Of Resi	stance Per Section In Ppm Per Deg Celsius:
-100.0/+100.0 single section	
Power Dissipation Rating Per Se	ction In Watts:
0.25 heat sink single section	
Resistance Tolerance Per Section	n In Percent:
-5.0/+5.0 single section	
Ambient Tempurature In Deg Ce	Isius Per Section At Full Rated Power:
85.0 single section	

NSN 5905-01-207-2420

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0