NSN 5905-01-207-2420

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-207-2420

vion orimio at mapolina orobacogi	54p.55.11#1161#65656 6 7 25 7 2 125
Section Quantity:	
1	
Body Style:	
Rectangular	
Reliability Indicator:	
Not established	
Terminal Length:	
Between 0.173 inches and 0.203	inches
Shaft Diameter:	
0.070 inches	
Shaft Length:	
Between 0.025 inches and 0.045	inches
Body Length:	
Between 0.230 inches and 0.270	inches
Body Width:	
Between 0.025 inches and 0.055	inches
Body Height:	
Between 0.230 inches and 0.270	inches
Shaft Style:	
Round, slotted	
Actuator Type:	
Single shaft	
Center To Center Distance Bety	veen Terminals:
0.100 inches	
Terminal Location:	
Rear end	
Mounting Method:	
Printed circuit	
Electrical Resistance Per Section	on:
50.000 ohms single section	
Center To Center Distance Betw	ween Center Terminal And Outside Terminal:
0.100 inches	
Ambient Tempurature In Deg C	elsius Per Section At Zero Percent Rated Power:
150.0 single section	
Tempurature Coefficient Of Res	sistance Per Section In Ppm Per Deg Celsius:
-100.0/+100.0 single section	
Power Dissipation Rating Per S	ection In Watts:
0.25 heat sink single section	
Resistance Tolerance Per Secti	on In Percent:
-5.0/+5.0 single section	
Ambient Tempurature In Deg C	elsius Per Section At Full Rated Power:
85.0 single section	

NSN 5905-01-207-2420

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0