## NSN 5905-01-207-3018

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-207-3018 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.625 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.219 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 1.215 inches **Undercut Diameter:** 0.125 inches **Shaft Style:** Round, stepped **Actuator Type:** Single shaft **Undercut Length:** 0.281 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Lower adjacent side two rows **Mounting Method:** Standard bushing **Features Provided:** Shaft seal **Electrical Resistance Per Section:** 1000.000 ohms single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

Power Dissipation Rating Per Section In Watts:

2.0 7th secondary finish

## NSN 5905-01-207-3018

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



## **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

**Special Features:** 

Resistor body is environmentally sealed, stepped shaft is flatted, inner shaft controls second resistor, outer shaft controls the resistor nearest the front

Γerminal	Type	And	Quantity	:
----------	------	-----	----------	---

3 wire loop

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0