Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-207-6436

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.010
Overall Length:
0.800 inches
Terminal Length:
0.300 inches
Overall Height:
0.375 inches
Overall Width:
0.170 inches
Shaft Diameter:
0.075 inches
Shaft Length:
0.080 inches
Body Length:
0.420 inches
Body Width:
0.170 inches
Body Height:
0.375 inches
Shaft Style:
Round, slotted
Shaft Bearing Type:
Sleeve
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
10800.0
Maximum Starting Torque:
5.00 inch-ounces
Maximum Running Torque:
5.00 inch-ounces
Center To Center Distance Between Terminals:
0.200 inches
Fragility Factor:
Moderately rugged

## NSN 5905-01-207-6436

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



**Terminal Location:** Rear end **Mounting Method:** Terminal **Cubic Measure:** 0.268 cubic inches **Electrical Resistance Per Section:** 1.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** 10800.0 Center To Center Distance Between Center Terminal And Outside Terminal: 0.100 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0/+100.0 single section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section **Standard Taper Curve Per Section:** A single section **Test Data Document:** 81349-mil-r-39035 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity: Specification Data:** 81349-mil-r-39035/2 government specification Shelf Life: Unit Of Measure: **Demilitarization:** A002a0

Clutch

3 pin

N/a

No Fiig: