

View Online at <https://aerobasegroup.com/nsn/5905-01-208-1181>

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

Between 0.870 inches and 0.880 inches

Shaft Diameter:

Between 0.2494 inches and 0.2497 inches

Shaft Length:

Between 0.781 inches and 0.843 inches

Mounting Bushing Length:

Between 0.307 inches and 0.317 inches

Body Length:

2.000 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

3600.0

Fragility Factor:

Moderately rugged

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Cubic Measure:

1.216 cubic inches

Electrical Resistance Per Section:

5.0 kilohms all sections

Rotary Actuator Travel In Angular Deg:

3600.0

Function Conformity Tolerance Per Section:

-0.15 to 0.15 all sections

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 all sections

Power Dissipation Rating Per Section In Watts:

5.0 free air all sections

Function Conformity Per Section:

All sections independent linearity

Resistance Tolerance Per Section In Percent:

-3.0 to 3.0 all sections

Actuator Travel Control Feature:

Stops

Function Characteristic Per Section:

All sections linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 all sections

Test Data Document:

08748-r+32 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0