

View Online at <https://aerobasegroup.com/nsn/5905-01-208-6333>

Section Quantity:

1

Body Style:

Cylindrical

Reliability Indicator:

Not established

Terminal Length:

0.547 inches

Body Diameter:

0.516 inches

Body Length:

0.688 inches

Actuator Type:

Flush drive with slot-hole

Effective Electrical Rotation In Deg Angular Rotation:

295.0

Maximum Starting Torque:

3.00 inch-ounces

Maximum Running Torque:

3.00 inch-ounces

Maximum Stop Torque:

10.00 inch-ounces

Mechanical Backlash In Deg Angular Rotation:

3.0

Center To Center Distance Between Terminals:

0.200 inches

Fragility Factor:

Moderately delicate

Terminal Location:

Rear end

Mounting Method:

Terminal

Features Provided:

Nonmetallic shaft

Electrical Resistance Per Section:

10.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

295.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

Resistance Temperature Characteristic Range Per Section In Percent:

+0.0 to 8.8 -55 degrees celsius single section and +0.0 to 4.4 -25 degrees celsius single section and +0.0 to 2.5 0 degrees celsius single section and -3.1 to 3.1 85 degrees celsius single section and +0.0 to 6.9 120 degrees celsius single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

Power Dissipation Rating Per Section In Watts:

0.125 free air single section

Resistance Tolerance Per Section In Percent:

-20.0 to 20.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0