

View Online at <https://aerobasegroup.com/nsn/5905-01-208-7705>

Section Quantity:

1

Body Style:

Rectangular bushing mounted

Reliability Indicator:

Not established

First Flat Length:

Between 0.495 inches and 0.505 inches

Flat Height:

Between 0.213 inches and 0.223 inches

Shaft Diameter:

Between 0.245 inches and 0.255 inches

Shaft Length:

Between 0.995 inches and 1.005 inches

Mounting Bushing Length:

Between 0.370 inches and 0.380 inches

Body Length:

Between 0.475 inches and 0.485 inches

Body Width:

Between 0.495 inches and 0.505 inches

Body Height:

Between 0.495 inches and 0.505 inches

Shaft Style:

Round, flatted

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Nonturn Device Location:

At 9 oclock

Fragility Factor:

Moderately rugged

Screw Thread Diameter:

Between 0.370 inches and 0.380 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Lower adjacent side single row

Mounting Method:

Standard bushing

Features Provided:

Humidity proof

Cubic Measure:

0.120 cubic inches

Electrical Resistance Per Section:

5.0 kilohms single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

Power Dissipation Rating Per Section In Watts:

0.25 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Standard Taper Curve Per Section:

M single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0