

View Online at <https://aerobasegroup.com/nsn/5905-01-208-7705>

**Section Quantity:**

1

**Body Style:**

Rectangular bushing mounted

**Reliability Indicator:**

Not established

**First Flat Length:**

Between 0.495 inches and 0.505 inches

**Flat Height:**

Between 0.213 inches and 0.223 inches

**Shaft Diameter:**

Between 0.245 inches and 0.255 inches

**Shaft Length:**

Between 0.995 inches and 1.005 inches

**Mounting Bushing Length:**

Between 0.370 inches and 0.380 inches

**Body Length:**

Between 0.475 inches and 0.485 inches

**Body Width:**

Between 0.495 inches and 0.505 inches

**Body Height:**

Between 0.495 inches and 0.505 inches

**Shaft Style:**

Round, flatted

**Shaft Bearing Type:**

Sleeve

**Actuator Type:**

Single shaft

**Nonturn Device Location:**

At 9 oclock

**Fragility Factor:**

Moderately rugged

**Screw Thread Diameter:**

Between 0.370 inches and 0.380 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Lower adjacent side single row

**Mounting Method:**

Standard bushing

**Features Provided:**

Humidity proof

**Cubic Measure:**

0.120 cubic inches

**Electrical Resistance Per Section:**

5.0 kilohms single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

120.0 single section

**Power Dissipation Rating Per Section In Watts:**

0.25 free air single section

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

25.0 single section

**Standard Taper Curve Per Section:**

M single section

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0