NSN 5905-01-209-4509

Film Fixed Resistor Network - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5905-01-209-4509 |
|--|
| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: |
| -50.0 to 50.0 first temp coefficient |
| Electrical Resistance: |
| 9.840 kilohms 3rd intermediate resistance value |
| Resistance Tolerance In Percent: |
| -0.500 to 0.500 each resistor |
| Ambient Tempurature In Deg Celsius At Full Rated Power: |
| 25.0 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| 85.0 |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: |
| -55.0 to 85.0 temp range of first temp coefficient |
| Inclosure Method: |
| Encapsulated |
| Terminal Quantity: |
| 16 |
| Terminal Type: |
| Tab, solder lug |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 0.125 inches |
| Body Length: |
| 0.870 inches |
| Body Width: |
| 0.260 inches |
| Body Height: |
| 0.200 inches |
| Err Default: |
| 0.018 inches |
| Identical Value Resistor Quantity: |
| 3 lowest resistance value |
| Style Designator: |
| Dual inline |
| Test Data Document: |
| 14304-10085-5610 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing |
| etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| |

No

Demilitarization:

NSN 5905-01-209-4509

Film Fixed Resistor Network - Page 2 of 2



Fiig:

A001a0