NSN 5905-01-210-3494

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-210-3494

-100.0 to 100.0 Electrical Resistance: 38.300 kilohms Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.380 inches and 1.620 inches Body Diameter: Between 0.094 inches and 0.165 inches Body Length: Between 0.313 inches and 0.437 inches Between 0.313 inches and 0.437 inches Err Default: 0.025 inches Criticality Code Justification: Zzzw Special Features: Temp coef not to exceed plus 500 ppm Style Designator: Axial terminal each end Departure From Cited Document: Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications Shelf Life: N/a Unit of Measure: Demilitarization: No Filig: A001a0	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
38.300 kilohms Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.380 inches and 1.620 inches Body Diameter: Between 0.094 inches and 0.165 inches Body Length: Between 0.313 inches and 0.437 inches Err Default: 0.025 inches Criticality Code Justification: Zzzw Special Features: Temp coef not to exceed plus 500 ppm Style Designator: Axial terminal each end Departure From Cited Document: Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	-100.0 to 100.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.380 inches and 1.620 inches Body Diameter: Between 0.094 inches and 0.165 inches Body Length: Between 0.0313 inches and 0.437 inches Err Default: 0.025 inches Criticality Code Justification: Zzzw Special Features: Temp coef not to exceed plus 500 ppm Style Designator: Axial terminal each end Departure From Cited Document: Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Electrical Resistance:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.380 inches and 1.620 inches Body Diameter: Between 0.094 inches and 0.165 inches Body Length: Between 0.313 inches and 0.437 inches Between 0.313 inches and 0.437 inches Err Default: 0.025 inches Criticality Code Justification: Zzzw Special Features: Temp coef not to exceed plus 500 ppm Style Designator: Axial terminal each end Departure From Cited Document: Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	38.300 kilohms
Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.380 inches and 1.620 inches Body Diameter: Between 0.094 inches and 0.165 inches Body Length: Between 0.313 inches and 0.437 inches Between 0.313 inches and 0.437 inches Err Default: 0.025 inches Criticality Code Justification: Zzzw Special Features: Temp coef not to exceed plus 500 ppm Style Designator: Axial terminal each end Departure From Cited Document: Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Inclosure Method:
Wire lead Reliability Indicator: Not established Terminal Length: Between 1.380 inches and 1.620 inches Body Diameter: Between 0.094 inches and 0.165 inches Body Length: Between 0.313 inches and 0.437 inches Err Default: 0.025 inches Criticality Code Justification: Zzzw Special Features: Temp coef not to exceed plus 500 ppm Style Designator: Axial terminal each end Departure From Cited Document: Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Encapsulated
Reliability Indicator: Not established Terminal Length: Between 1.380 inches and 1.620 inches Body Diameter: Between 0.094 inches and 0.165 inches Body Length: Between 0.313 inches and 0.437 inches Err Default: 0.025 inches Criticality Code Justification: Zzzw Special Features: Temp coef not to exceed plus 500 ppm Style Designator: Axial terminal each end Departure From Cited Document: Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Terminal Type:
Note stablished Terminal Length: Between 1.380 inches and 1.620 inches Body Diameter: Between 0.094 inches and 0.165 inches Body Length: Between 0.313 inches and 0.437 inches Err Default: 0.025 inches Criticality Code Justification: Zzzw Special Features: Temp coef not to exceed plus 500 ppm Style Designator: Axial terminal each end Departure From Cited Document: Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Wire lead
Terminal Length: Between 1.380 inches and 1.620 inches Body Diameter: Between 0.094 inches and 0.165 inches Body Length: Between 0.313 inches and 0.437 inches Err Default: 0.025 inches Criticality Code Justification: Zzzw Special Features: Temp coef not to exceed plus 500 ppm Style Designator: Axial terminal each end Departure From Cited Document: Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Reliability Indicator:
Between 1.380 inches and 1.620 inches Body Diameter: Between 0.094 inches and 0.165 inches Body Length: Between 0.313 inches and 0.437 inches Err Default: 0.025 inches Criticality Code Justification: Zzzw Special Features: Temp coef not to exceed plus 500 ppm Style Designator: Axial terminal each end Departure From Cited Document: Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Not established
Between 0.094 inches and 0.165 inches Body Length: Between 0.313 inches and 0.437 inches Err Default: 0.025 inches Criticality Code Justification: Zzzw Special Features: Temp coef not to exceed plus 500 ppm Style Designator: Axial terminal each end Departure From Cited Document: Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Terminal Length:
Between 0.094 inches and 0.165 inches Body Length: Between 0.313 inches and 0.437 inches Err Default: 0.025 inches Criticality Code Justification: Zzzw Special Features: Temp coef not to exceed plus 500 ppm Style Designator: Axial terminal each end Departure From Cited Document: Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Between 1.380 inches and 1.620 inches
Between 0.313 inches and 0.437 inches Err Default: 0.025 inches Criticality Code Justification: Zzzw Special Features: Temp coef not to exceed plus 500 ppm Style Designator: Axial terminal each end Departure From Cited Document: Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Diameter:
Between 0.313 inches and 0.437 inches Err Default: 0.025 inches Criticality Code Justification: Zzzw Special Features: Temp coef not to exceed plus 500 ppm Style Designator: Axial terminal each end Departure From Cited Document: Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Between 0.094 inches and 0.165 inches
Err Default: 0.025 inches Criticality Code Justification: Zzzw Special Features: Temp coef not to exceed plus 500 ppm Style Designator: Axial terminal each end Departure From Cited Document: Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Length:
Criticality Code Justification: Zzzw Special Features: Temp coef not to exceed plus 500 ppm Style Designator: Axial terminal each end Departure From Cited Document: Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Between 0.313 inches and 0.437 inches
Criticality Code Justification: Zzzw Special Features: Temp coef not to exceed plus 500 ppm Style Designator: Axial terminal each end Departure From Cited Document: Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Err Default:
Special Features: Temp coef not to exceed plus 500 ppm Style Designator: Axial terminal each end Departure From Cited Document: Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.025 inches
Special Features: Temp coef not to exceed plus 500 ppm Style Designator: Axial terminal each end Departure From Cited Document: Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Criticality Code Justification:
Temp coef not to exceed plus 500 ppm Style Designator: Axial terminal each end Departure From Cited Document: Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Zzzw
Style Designator: Axial terminal each end Departure From Cited Document: Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Special Features:
Axial terminal each end Departure From Cited Document: Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Temp coef not to exceed plus 500 ppm
Departure From Cited Document: Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal each end
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Departure From Cited Document:
N/a Unit Of Measure: Demilitarization: No Fiig:	Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
Demilitarization: No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
-	No
A001a0	Fiig:
	A001a0