Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-211-1434

# Section Quantity:

1

Body Style:

Rectangular

**Reliability Indicator:** 

Established

#### Reliability Failure Rate Level In Percent:

0.010

**Terminal Length:** 

0.300 inches

Shaft Diameter:

0.075 inches

Shaft Length:

0.080 inches

Body Length:

### 0.375 inches

**Body Width:** 

0.170 inches

Body Height:

0.375 inches

Shaft Style:

Round, slotted

## Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

10800.0

Maximum Starting Torque:

5.00 inch-ounces

Maximum Running Torque:

5.00 inch-ounces

#### Center To Center Distance Between Terminals:

0.200 inches

Fragility Factor:

Moderately rugged

**Terminal Location:** 

Left adjacent side two rows

**Mounting Method:** 

Terminal

#### Center To Center Distance Between Terminal Rows:

0.100 inches

# NSN 5905-01-211-1434

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



# **Cubic Measure:** 0.024 cubic inches **Electrical Resistance Per Section:** 5.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** 10800.0 Center To Center Distance Between Center Terminal And Outside Terminal: 0.100 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -100.0/+100.0 single section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section **Standard Taper Curve Per Section:** A single section **Test Data Document:** 81349-mil-r-39035 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 3 pin **Specification Data:** 81349-mil-r-39035/2 government specification Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A002a0